

Class II B2 Biological Safety Cabinet Cytotoxic Safety Cabinet

Three protection: operator, sample and environment.

Airflow system: 0% air recirculation, 100% air exhaust.


B2 Biological Safety Cabinet has higher class of safety protection compared with type A2. It may be used for work with volatile toxic chemicals and radionuclides as required, as adjuncts to microbiological studies.

Cytotoxic Safety Cabinet


BIOBASE Cytotoxic Safety Cabinet is the premium solution for cytotoxic / antineoplastic drug processing, providing the highest level of patient, pharmacist and environmental protection.

The unique demands of handling and preparing cytotoxic drugs for use in chemotherapy require a specialized cabinet.

Cytotoxic Safety Cabinet



Class II B2 Biological Safety Cabinet





Class II B2 Biological Safety Cabinet



Work Zone
Work zone, made of 304 stainless steel, is surrounded by negative pressure.



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.



Foot Switch
Adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement.



Remote Control
All functions can be realized with it, making the operation much easier and more convenient.



Front Window
Two-layer laminated toughened glass5mm, anti UV



Waterproof Socket
2 waterproof sockets are located in the side wall, for optimum convenience of using small devices inside the cabinet.



Footmaster Caster
Universal caster with brake and leveling feet



Exhaust Blower
Centrifugal fan, speed adjustable.

ADVANTAGE

1. Time reserve function.
2. Motorized front window.
3. HEPA filter life and UV life indicator.
4. Automatic air speed adjustable with filter block.
5. Work area surrounded by negative pressure, it can ensure maximum safety in work area.
6. Most accessories are standard, which saves your money. There is no need to pay more.
7. Audio and visual alarm (filter replacement, window over height, abnormal air flow velocity, etc).
8. Remote control. All functions can be realized with it, making the operation much easier and more convenient.
9. Interlock function: UV lamp and front window; UV lamp and blower; fluorescent lamp; blower and front window
10. Foot switch. Adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement.

TECHNICAL PARAMETERS

Model	BSC-1100IB2-X	BSC-1300IB2-X	BSC-1500IB2-X	BSC-1800IB2-X
Internal Size (W*D*H)	940*600*660mm	1150*600*660mm	1350*600*660mm	1670*600*660mm
External Size (W*D*H)	1100*750*2250mm	1300*750*2250mm	1500*760*2250mm	1820*750*2250mm
Tested Opening	Safety Height 200mm(8")			
Max Opening	420 mm (17")			
Inflow Velocity	0.53±0.025m/s			
Downflow Velocity	0.33±0.025m/s			
Pre-Filter	Washable			
HEPA Filter	Two, 99.999% efficiency at 0.3µm, filter life indicator.			
Front Window	Motorized, two-layer laminated toughened glass ≥ 5mm, anti UV			
Noise	NSF 49 ≤ 61dB / EN 12469 ≤ 58dB			
UV Lamp	30W*1	18W*1	40W*1	40W*2
Fluorescent Lamp	21W*2	21W*2	28W*2	40W*2
Illumination	≥1000Lux			
Consumption	700W	850W	900W	1200W
Waterproof Sockets	Two, total load of two sockets: 500W			
Display	LCD display, exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.			
Control System	Microprocessor			
Airflow System	0% air re-circulation, 100% air exhaust			
Visual and Audio Alarm	Filter replacement, window over height, abnormal air flow velocity			
Exhaust Duct	4 meters PVC duct, Diameter:300mm			
Material	Work Zone: 304 stainless steel Main Body: Cold-rolled steel with anti-bacteria powder coating			
Work Surface Height	750mm			
Caster	Footmaster caster			
Power Supply	AC 220V±10%, 50/60Hz; 110V±10%, 60Hz (110V/60Hz is not applicable to BSC-1800IB2-X)			
Standard Accessory	Fluorescent lamp, UV lamp*2, base stand, remote control, foot switch, exhaust blower, exhaust duct, drain valve, waterproof sockets*2, pipe strap*2			
Optional Accessory	Water and gas tap			
Gross Weight	246kg	276kg	302kg	408kg
Package	Main Body	1220*1000*1840mm	1460*1050*1800mm	1650*990*1950mm
	Exhaust Blower (W*D*H)	970*810*630mm	970*810*630mm	970*810*630mm